

SET® 2' x 2' and 2' x 4' Steel Frame LED Troffer





Features

- Available with Frosted or Prismatic diffuser
- Instant on to full brightness
- High efficacy at 112-120 lumens per watt
- 7 year warranty
- Available 3500-5700 lumen packages
- Suitable for damp locations
- Superior heat management yields 60,000 hours life
- Lower maintenance costs
- Prism lens
- Plenum Rated

- 0-10 V DC dimming capability
- UL, DLC, RoHS and FCC certified
- Light-gauge metal frame for added durability
- Isolated type power driver is shock and fire resistant
- Workable Voltage 90-305V

Applications

- Office
- Workshop
- Indoor area lighting
- · Healthcare facilities
- Schools
- Retail stores

Ord	ering	Infort	nation:

Ex. MTR22-5L-40K-UL-AP-FI

Model	
MTR22 = 2' x	2'
MTD24 - 21	41

Lumen Package $3L = 3600Lm, 36W = 2' \times 2'$

 $4L = 4000Lm, 40W = 2' \times 4'$ $5L = 5592 \text{ Lm}, 49.6W = 2' \times 2'$

5L = 5715 Lm, 48W = 2' x 2'

 $5L = 5736 \text{ Lm}, 50W = 2' \times 4'$

CCT

30K = 3000K

40K = 4000K

50K = 5000K57K = 5700K Voltage

UL= 120-277V

UH=347-480V

Lens

AP = Acrylic Prismatic FR = Frosted

Driver Mounting

ID = Integrated Driver (attached) **FI** = Field Install (unattached)











