



Features

- L70 >60,000 hours at 85°C
- Frosted lens to reduce glare
- Instant on to full brightness
- High efficacy at 100-108 lumens per watt
- Available 3500K, 4000K, and 5000K color temperatures
- Suitable for damp locations
- Lower maintenance costs
- Dimensions 47.7" x 11.7" x 4.3" (1x4)
- Dimensions 23.7" x 23.7" x 4.3" (2x2)
- Dimensions 47.7" x 23.7" x 4.3" (2x4)
- LM79/80 reports and TM21 data available
- Ultra lightweight for easy installation
- Operating temp -40°C - +60°C / -40°F - +140°F

- 0-10 V DC dimming standard
- UL, DLC, RoHs and FCC certified
- Isolated type power driver is shock and fire resistant
- 7 year warranty
- Workable Voltage 90-305V

Applications

- Office
- Workshop
- Indoor area lighting
- Healthcare facilities
- Schools
- Retail stores

Ordering Information:

Ex. TR24-8L-50K-UL



Model

TR14 = 1' x 4'
 TR22 = 2' x 2'
 TR24 = 2' x 4'

Lumen Package

4L = 3,500 Lm, 35W¹
 5L = 5,000 Lm, 50W²
 8L = 8,000 Lm, 80W³

CCT

35K = 3500K
 40K = 4000K
 50K = 5000K⁴

Voltage

UL = 120-277V

- 1 = Only Available with TR14 and TR22
 2 = Only Available with TR22 and TR24
 3 = Only Available with TR24
 4 = Only Available with TR24 - 8L

