



Features:

- Rugged die cast aluminum construction
- IP68 rated for highest ingress protection
- Integrated wall mount bracket
- Easy plug-and-play installation
- Operating temp -30°C to 50°C/ -22°F to 122°F
- Workable voltage 90-305V
- Up to 80% savings over comparable HPS or MH fixtures
- Sealed fixture rated for class 1 division 2 hazardous location Group A, B, C & D
- 100 Lumens per Watt
- Surge protection: IEC/EN 61000-4-5

- UL, DLC, RoHS, and FCC certified
- 5 and 10 year* warranty available
- RoHS Compliant-no toxic chemicals
- 40W = 7.87" x 7.87" x 10.63"
- 100W = 11.8" x 11.8" x 6.89"
- 185W = 15.75" x 15.75" x 7.3"

Applications:

- Oil refinery
- Petroleum
- Steel mills
- Chemical
- Paint booths
- Wastewater treatment

Ordering Information:

EX. HL-10L-57K-UL-5

Model	Lumen Package	CCT	Voltage	Warranty
HL	4L = 4,000 Lm, 40W 10L = 10,000 Lm, 100W 20L = 20,000 Lm, 200W	57K = 5700K	UL = 120-277V UH = 347-480V	5 = 5 years 10 = 10 years

*10 year warranty available for additional charge