



## Features:

- Rugged die cast aluminum construction
- IP68 rated for highest ingress protection
- Integrated wall mount bracket
- Easy plug-and-play installation
- Operating temp -30°C to 50°C/  
-22°F to 122°F
- Workable voltage 90-305V
- Up to 80% savings over comparable HPS or MH fixtures
- Sealed fixture rated for class 1 division 2 hazardous location Group A, B, C & D
- 100 Lumens per Watt
- Surge protection: IEC/EN 61000-4-5

- UL, DLC, RoHS, and FCC certified
- 5 and 10 year\* warranty available
- RoHS Compliant-no toxic chemicals
- 40W = 7.87" x 7.87" x 10.63"
- 100W = 11.8" x 11.8" x 6.89"
- 185W = 15.75" x 15.75" x 7.3"

## Applications:

- Oil Refinery
- Steel Mills
- Petroleum
- Chemical
- Paint booth
- Wastewater treatment

### Items Stocked in Illinois Warehouse

Model Number	Lumens	Input Voltage	Color Temp (K)	Watts	Lumens Per Watt	Warranty
HL-4L-57K-UL-5	4000	120-277V	5700	40	100	5
HL-10L-57K-UL-5	10,000	120-277V	5700	100	100	5
HL-20L-57K-UL-5	20,000	120-277V	5700	200	100	5
HL-4L-57K-UL-10	4000	120-277V	5700	40	100	10
HL-10L-57K-UL-10	10,000	120-277V	5700	100	100	10
HL-20L-57K-UL-10	20,000	120-277V	5700	200	100	10

\*10 year warranty available for additional charge

