



## Features

- Frosted lens to reduce glare with 14% uplight
- Instant on to full brightness
- Energy efficient
- Wide light distribution
- High efficacy up to 134 lumens per watt
- Light weight for easy installation
- Lower maintenance costs
- Available 3000K, 3500K, 4000K, and 5000K color temperatures
- Operating temp -40°C - +60°C  
-40°F - +140°F
- Dimensions 21.6" x 21.6" x 5.20"
- LM79/80 reports and TM21 data available

- Input voltage 120-277V
- Workable Voltage at 90-305V or 312-528V
- UL, RoHS and FCC certified
- 7 year warranty
- L70 >60,000 hours at 85°C
- 0-10 V DC dimming standard

## Applications

- Warehouses
- Storage areas
- Cold storage
- Convention centers
- Airports
- Healthcare facilities
- Workshops
- Manufacturing plants

Reference Number	Model Number	Lumens	CRI	Color Temperature(K)	Watts	Lumens Per Watt	DLC	IES
61061	LBP-11L-40K-UL	14,505	>80	4000	100	143	V5.0 P	
61062	LBP-11L-50K-UL	14,631	>80	5000	101	144	V5.0 P	
61063	HBP-18L-40K-UL	18,144	>80	4000	133	135	V5.0 P	
61064	HBP-18L-50K-UL	18,332	>80	5000	134	136	V5.0 P	
61065	HBP-24L-40K-UL	27,706	>80	4000	201	137	V5.0 P	
61066	HBP-24L-50K-UL	28,004	>80	5000	202	138	V5.0 P	