



## Features

- Frosted lens to reduce glare
- Instant on to full brightness
- Energy efficient
- Wide light distribution
- High efficacy at 142 lumens per watt
- Light weight for easy installation
- Lower maintenance costs
- Available 3000K, 4000K, and 5000K color temperatures
- IP65 Rated for wet locations
- Operating temp -40°C - +60°C  
-40°F - +140°F
- Dimensions 21.6" x 21.6" x 5.20"
- LM79/80 report available
- TM21 **Reported Values** as listed in DLC QPL
- TM21 **Calculated Values** subject to manufacturer's interpretation and available on request.
- 7 year warranty
- 0-10 V DC dimming standard

- DLC Premium 5.1 under Nuwave except HBS-18L and HBS-28L DLC Standard except
- UL, RoHS and FCC certified
- NSF certified-Splash zone/Non-Food zone
- Input voltage 120-277V (UL) or 347-480V (UH)
- Workable voltage at 90-305V or 312-528V
- Field Replaceable driver
- CRI > 84

## Applications

- Warehouses
- Storage areas
- Food processing plants
- Cold storage
- Convention centers
- Airports
- Healthcare facilities
- Manufacturing plants
- Food Processing
- Agriculture

## Available Options

- 6' cord and plug
- Cable suspension system
- Stainless steel wire guard
- Occupancy sensor/Daylight harvesting
- Pendant hook

## Items Stocked in Illinois Warehouse

Model Number	Reference #	Lumens	Color Temp (K)	Watts	Lm/W	Wattage Equivalent	
HB-18L-30K-UL	60546	16,801	3000K	136	123	400W HID	**
HB-18L-40K-UL-MW	61684	18,191	4000K	130.4	139.5	400W HID	
HB-18L-40K-UL-SS	62180	18,191	4000K	130.4	139.5	400W HID	
HB-18L-50K-UH	52311	19,000	5000K	136.1	139.63	400W HID	
HB-18L-50K-UH-SS	62183	19,000	5000K	136.1	139.63	400W HID	
HB-18L-50K-UL-MW	61685	18,604	5000K	131.3	141.69	400W HID	
HB-18L-50K-UL-SS	62181	18,604	5000K	131.3	141.69	400W HID	
HBS-18L-40K-UL	61111	16,111	4000K	137	117.91	400W HID	
HBS-18L-40K-UL-SS	62190	16,111	4000K	136.6	117.91	400W HID	
HBS-18L-50K-UL	60474	16,633	5000K	137	118.98	400W HID	
HBS-18L-50K-UL-SS	62191	16,633	5000K	139.8	118.98	400W HID	
HBS-24L-40K-UL	61131	26,945	4000K	195	142.65	1000W HID	
HBS-24L-40K-UL-SS	62194	26,945	4000K	188.9	142.65	1000W HID	
HBS-24L-50K-UH	61333	26,746	5000K	222	148.42	1000W HID	
HBS-24L-50K-UL	61132	27,503	5000K	187.8	146.45	1000W HID	
HBS-24L-50K-UL-SS	62195	27,503	5000K	187.8	146.45	1000W HID	
HB-28L-40K-UL	52050	28,333	4000K	232	122.17	1000W HID	**
HB-28L-40K-UL-MW	61687	29,729	4000K	221.3	134.36	1000W HID	
HB-28L-40K-UL-SS	62184	29,729	4000K	221.3	134.36	1000W HID	
HB-28L-50K-UH	52411	29,305	5000K	213.5	137.26	1000W HID	
HB-28L-50K-UH-SS	62187	29,305	5000K	213.5	137.26	1000W HID	
HB-28L-50K-UL-MW	61688	30,197	5000K	218.8	138.01	1000W HID	
HB-28L-50K-UL-SS	62185	30,197	5000K	218.8	138.01	1000W HID	
HBS-28L-35K-UL	61115	27,212	3500K	217	125	1000W HID	**

\* Replacement to be same Model# with MW suffix

MW = Mean Well Driver

SS = Sosen Driver

\*\* Not on DLC List