



## Features

- Frosted lens to reduce glare
- Instant on to full brightness
- Energy efficient
- Wide light distribution
- High efficacy at 142 lumens per watt
- Light weight for easy installation
- Lower maintenance costs
- Available 4000K and 5000K color temperatures
- IP65 Rated for wet locations
- Operating temp -40°C - +60°C  
-40°F - +140°F
- Dimensions 21.6" x 21.6" x 5.20"
- Installs by 3/4" threaded pipe, griplock system or hook mounting
- L70 >60,000 hours at 85°C
- 0-10 V DC dimming standard
- UL, DLC premium 5.0, RoHs and FCC certified
- 7 year warranty
- Workable Voltage at 90-305V, or 180-528V
- NSF certified (Splash zone/Non food zone)

## Applications

- Indoor/outdoor lighting
- Warehouses
- Storage areas
- Retail stores
- Malls
- Convention centers
- Airports

### Ordering Information:

Ex. LB-8L-50K-UL-WG



#### Model

LB

#### Lumen Package

8L = 9,000 lm

11L = 14,000 lm

#### CCT

30K = 3,000K

35K = 3,500K

40K = 4,000K

50K = 5,000K

#### Voltage

UL = 120-277V

UH = 347-480V

#### Options

OS = Occupancy Sensor set

CR = Commissioning Remote (for OS)

WG = Wireguard

CD = 6' S/O cord

PS1 = 120V Straight blade plug

PS2 = 277V Straight blade plug

PT1 = 120V Twist-Lock plug

PT2 = 277V Twist-Lock plug

PH = Pendant Hook

EM = Emergency Battery Back Up

Y3 = Y-3 Wired Grippler