



Features

- Frosted lens to reduce glare
- Instant on to full brightness
- Energy efficient
- Wide light distribution
- High efficacy at 142 lumens per watt
- Light weight for easy installation
- Lower maintenance costs
- Available 4000K and 5000K color temperatures
- IP65 Rated for wet locations
- Operating temp -40°C - +60°C
-40°F - +140°F
- Dimensions 21.6" x 21.6" x 5.20"
- Installs by 3/4" threaded pipe, griplock system or hook mounting
- L70 >60,000 hours at 85°C
- 0-10 V DC dimming standard
- UL, DLC premium 5.0, RoHs and FCC certified
- 7 year warranty
- Workable Voltage at 90-305V, or 180-528V
- NSF certified (Splash zone/Non food zone)

Applications

- Indoor/outdoor lighting
- Warehouses
- Storage areas
- Retail stores
- Malls
- Convention centers
- Airports

Ordering Information:

Ex. LB-8L-50K-UL-WG



<u>Model</u>	<u>Lumen Package</u>	<u>CCT</u>	<u>Voltage</u>	<u>Options</u>
LB	8L = 9,000 lm 11L = 14,000 lm	30K = 3,000K 35K = 3,500K 40K = 4,000K 50K = 5,000K	UL = 120-277V UH = 347-480V	OS = Occupancy Sensor set CR = Commissioning Remote (for OS) WG = Wireguard CD = 6' S/O cord PS1 = 120V Straight blade plug PS2 = 277V Straight blade plug PT1 = 120V Twist-Lock plug PT2 = 277V Twist-Lock plug PH = Pendant Hook EM = Emergency Battery Back Up Y3 = Y-3 Wired Grippler

