



Features

- E39 Mogul base - Standard Socket
- Instant on to full brightness
- Operates without ballast- bypass ballast
- Wide light distribution
- 120-125 lumens per watt
- Light weight for easy installation
- Lower maintenance costs
- 360 degree beam angle
- Flame retardant material
- IP64 waterproof design
- Isolated driver better for heat dissipation
- Dimensions:
 - > 58113: 3.66" x 10.79" MOL
 - > 58123: 5.52" x 11.34" MOL
 - > 58133: 5.52" x 13.71" MOL
- Superior heat management
- Certificate: CE, RoHS, UL /cUL
- No fan heat dissipation solution
- 5 year warranty
- Input voltage 100-277V
- Power factor >0.9
- Operating temp -30°C - +60°C/ -22°F - +140°F
- Fits most standard acorn style exterior fixtures

Applications

- Indoor/outdoor lighting
- Warehouse
- Street lights
- Bollards

Items Stocked in Illinois Warehouse

Reference Number	Model Number	Lumens	CRI	Color Temperature(K)	Watts	Lumens Per Watt	Wattage Equivalent
58113	CO-5L-50K-UL-E39	5,400	>80	5000	45	120	75W HID
58123	CO-10L-50K-UL-E39	10,000	>80	5000	80	125	250W HID
58133	CO-16L-50K-UL-E39	15,625	>80	5000	125	125	400W HID