



Features

- Center Basket Design
- Instant on to full brightness
- High efficacy at 140+ lumens per watt
- 7 year warranty
- Available 4000-7000 lumen packages
- Suitable for damp locations
- 2'x2' and 2'x4' models available
- CRI >80
- Highly reflective matte white paint finish
- Operating temp -40°C to +60°C
- 0-10 V DC dimming standard

- ETL, DLC Premium, RoHS and FCC certified
- Workable Voltage 90-305V
- Compatible with most lighting controls

Applications

- Office
- Indoor area lighting
- Healthcare facilities
- Schools
- Retail stores

Options

- Battery Back up unit #62998

Model Number	Reference #	Lumens	Color Temp (°K)	Watts	Lm/W	Input Voltage
TRK22-4L-40K-UL	61350	4272	4000	31	138	120-277 V
TRK22-4L-50K-UL	60731	4316	5000	31	141	120-277 V
TRK22-5L-40K-UL	61351	5145	4000	39	134	120-277 V
TRK22-5L-50K-UL	60732	5450	5000	38	144	120-277 V
TRK24-5L-40K-UL	61352	5482	4000	39	142	120-277 V
TRK24-5L-50K-UL	60733	5526	5000	39	144	120-277 V
TRK24-7L-40K-UL	61353	6549	4000	47	140	120-277 V
TRK24-7L-50K-UL	60734	6942	5000	47	148	120-277 V

Testing Report

