



Features:

- Wide Beam Angle
- Built in aluminum heat sink , with 94 V0 Fire-Rated PC housing
- TC Model = IP65 rated (With PG9 connector)
- TS Model = Damp rated
- End knock out and Back knock out permits conduit connection on TC Model
 - **Input Voltage** : 120 - 277 VAC
 - **Power** : 25W - 70W
 - **Frequency** : 50 / 60 Hz
 - **Lumen Efficacy** : 120 lumens per watt
 - **Operating Temperature** : -25°F - + 40°C
 - **Power Factor** : >0.9
 - **Beam Angle** : 270°
 - **THD**: <18%
 - **Lifespan** : 50,000 hours
 - Warranty : 5 years
 - Color Temperature : 4000K - 5000K in stock Dimming
- Fixture comes with 5' mounting/hanging kit included
- 5 year warranty
- Full range of options: Emergency backup, Occupancy sensor, 0-10V Dimming, Tandem wiring, Cords
- TS = Need Cord at Start of each continuous run
- TC = 1/2" knock out and PG9 connector included
- ST: Stairwell with occupancy sensor that never turns off



Options :

- **OC** : Occupancy Sensor
- **EM** : Emergency Back-up - 90 minutes operation (Emergency operating temperature -13°F - +104°F) Remote required for testing
- **Cords**


Continuous Rows Max wattage 400 watts on 120V
1,000 watts on 277V



TPAL-TC



TPAL-TS



TS	Model#	Ref#	Lumens	LmW	Color Temp (°K)	Watt
24" Strip TS	TPAL24-2L-40K-UL-DM-TS	61244	2330	116	4000	20
48" Strip TS	TPAL48-4L-35K-UL-TS	61511	4308	119	3500	36
48" Strip TS	TPAL48-4L-40K-UL-TS	61226	5377	121	4000	36
48" Strip TS	TPAL48-4L-40K-UL-DM-TS	61246	5377	121	4000	36
48" Strip TS	TPAL48-4L-50K-UL-TS	61140	5515	125	5000	36
48" Strip TS	TPAL48-5L-35K-UL-TS	61541	5214	115	3500	45
48" Strip TS	TPAL48-5L-35K-UL-OC-TS	61543	5214	115	3500	45
48" Strip TS	TPAL48-5L-35K-UL-EM-TS	61544	4989	117	3500	43
48" Strip TS	TPAL48-5L-35K-UL-DM-TS	61542	5214	115	3500	45
48" Strip TS	TPAL48-5L-40K-UL-TS	61227	4989	127	4000	43
48" Strip TS	TPAL48-5L-50K-UL-TS	61228	6794	122	5000	45
96" Strip TS	TPAL96-8L-35K-UL-TS	61519	8677	128	3500	68
96" Strip TS	TPAL96-8L-40K-UL-TS	61253	10453	129	4000	68
96" Strip TS	TPAL96-8L-40K-UL-DM-TS	61254	10453	129	4000	68
96" Strip TS	TPAL96-8L-50K-UL-TS	61269	10654	130	5000	69
TS Cord	TS Cord with Special End	61331				
TC	Model#	Ref#	Lumens	LmW	Color Temp (°K)	Watt
24" Strip TC	TPAL-24-2L-35K-UL-TC	61508	2291	117	3500	20
24" Strip TC	TPAL24-2L-40K-UL-TC	61275	2330	119	4000	20
24" Strip TC	TPAL24-2L-40K-UL-OC-TC	61277	2330	119	4000	20
24" Strip TC	TPAL24-2L-40K-UL-OC-ST-TC	61628	2330	119	4000	20
24" Strip TC	TPAL24-2L-50K-UL-TC	61293	2407	124	5000	20
24" Strip TC	TPAL24-2L-50K-UL-OC-TC	61295	2407	124	5000	20
24" Strip TC	TPAL24-2L-50K-UL-OC-ST-TC	61631	2407	124	5000	20
48" Strip TC	TPAL48-4L-35K-UL-TC	61510	4308	119	3500	36
48" Strip TC	TPAL48-4L-35K-UL-OC-TC	61509	4308	119	3500	36
48" Strip TC	TPAL48-4L-40K-UL-TC	61278	5377	121	4000	36
48" Strip TC	TPAL48-4L-40K-UL-OC-TC	61280	5377	121	4000	36
48" Strip TC	TPAL48-4L-50K-UL-TC	61296	5515	125	5000	36
48" Strip TC	TPAL48-4L-50K-UL-OC-TC	61298	5515	126	5000	36
48" Strip TC	TPAL48-5L-35K-UL-OC-TC	61513	5214	115	3500	45
48" Strip TC	TPAL48-5L-35K-UL-OC-EM-TC	61512	4308	119	3500	45
48" Strip TC	TPAL48-5L-40K-UL-TC	61281	5301	117	4000	45
48" Strip TC	TPAL48-5L-40K-UL-EM-TC	61284	6650	117	4000	45
48" Strip TC	TPAL48-5L-40K-UL-OC-TC	61283	6794	117	4000	45
48" Strip TC	TPAL48-5L-40K-UL-OC-EM-ST-TC	61629	6650	117	4000	43
48" Strip TC	TPAL48-5L-50K-UL-TC	61299	6795	122	5000	45
48" Strip TC	TPAL48-5L-50K-UL-DM-TC	61300	5479	121	5000	45
48" Strip TC	TPAL48-5L-50K-UL-EM-TC	61302	6794	121	5000	44
48" Strip TC	TPAL48-5L-50K-UL-OC-EM-ST-TC	60632	5476	122	5000	45
96" Strip TC	TPAL96-8L-35K-UL-EM-TC	61516	8677	128	3500	68
96" Strip TC	TPAL96-8L-35K-UL-OC-TC	61517	8677	128	3500	68
96" Strip TC	TPAL96-8L-35K-UL-TC	61518	8677	128	3500	68
96" Strip TC	TPAL96-8L-40K-UL-EM-TC	61290	10453	115	4000	69
96" Strip TC	TPAL96-8L-40K-UL-OC-EM-ST-TC	61630	10453	115	4000	69
96" Strip TC	TPAL96-8L-40K-UL-OC-TC	61289	10453	115	4000	69
96" Strip TC	TPAL96-8L-40K-UL-TC	61287	10654	129	4000	67
96" Strip TC	TPAL96-8L-50K-UL-EM-TC	61308	10054	119	5000	71
96" Strip TC	TPAL96-8L-50K-UL-OC-EM-ST-TC	61633	8944	119	5000	69
96" Strip TC	TPAL96-8L-50K-UL-OC-TC	61307	10654	119	5000	71
96" Strip TC	TPAL96-8L-50K-UL-TC	61305	10654	119	5000	71
TC Cord	TC Cord w/NEMA 1-15 plug (120V)	61311				
TC - ST	Model#	Ref#	Lumens	LmW	Color Temp (°K)	Watt
24" Strip TC	TPAL24-2L-40K-UL-OC-ST-TC	61628	2330	119	4000	20
24" Strip TC	TPAL24-2L-50K-UL-OC-ST-TC	61631	2407	124	5000	20
48" Strip TC	TPAL48-5L-40K-UL-OC-EM-ST-TC	61629	4989	117	4000	43
48" Strip TC	TPAL48-5L-50K-UL-OC-EM-ST-TC	60632	5476	122	5000	45
96" Strip TC	TPAL96-8L-40K-UL-OC-EM-ST-TC	61630	7895	115	4000	69
96" Strip TC	TPAL96-8L-50K-UL-OC-EM-ST-TC	61633	8944	119	5000	69
TC Cord	TC Cord w/NEMA 1-15 plug (120V)	61311				
REMOTES	Model#	Ref#				
	RMSTOC	61696				
	RMSTEM	61324				

Specification/Product Parameters


- **Input voltage:** 120 - 277VAC
- **Power:** 20W-70W
- **Frequency:** 50/60Hz
- **Lumen Efficacy:** 120LM/W
- **Operating temperature:** -25° - +40° (Emergency minimum temperature -10°C)
- **Power factor:** > 0.9
- **Beam angle:** 270°
- **THD:** < 18%
- **Lifespan:** 50,000 H

60805	TPAL48-5L-40K-UL-DM-EM	5301 Lumens
4000 CCT	117 LmW	45 Watt
61301	TPAL48 5L 40K UL EM DM TC	4989 Lumens
4000 CCT	117 LmW	42.5 Watt

TS = Tandem Seamless
 TC = Tandem Cord/Conduit
 OC = Occupancy Sensor
 EM = Emergency Backup
 Lumen Output :
 48"=744LM; 96"=760 LM
 ST = Stairwell


Installation Instructions

Cable Suspension




Step (1)

Stem Mount



Step (2)

Ceiling or Wall Mount



Step (3)

Included With Each Fixture



(Hanging Kits)



(PG 9 connector)



(connector for seamless connection)



(Mounting Bracket)

Optional



Diagram of remote control(Emergency)

Dimension



Type TS



Type TC

Model	L(inches)		L2 (Inches)	W (Inches)	H (Inches)
	TS	TC	TS / TC	TS / TC	TS / TC
TPAL24	23.6	25.6	21.3	3.7	2.4
TPAL48	47.2	49.2	44.9	3.7	2.4
TPAL96	94.5	96.5	92.1	3.7	2.4

Model No.	Net Weight (LBS)	Qty(pcs /CTN)	Gross Weight/CTN(LBS)	Carton Size (Inches)
TPAL24	14.55	6	17.11	L30.32*W9.06*H9.25
TPAL48	23.55	6	28.35	L53.94*W9.06*H9.25
TPAL96	47.09	6	56.70	L101.18*W9.06*H9.25


Product Application Instructions-Sensor (Occupancy Sensor)

Standard Setting (Other Settings Available and need to be identified when order is placed)

Occupancy Sensor Hold Time	1 Minute	3 Minutes	5 Minutes	Custom
Sensor to Dim Level	20%	30%	50%	Custom
Sensor Stand by Period	1 Minute	5 Minutes	10 Minutes	Disable

Emergency Remote Controller (Required)

- High Temp. Ni-MH battery. Compact in size, longer lifetime, safer in practical use, RoHS compliant
- The nickel-metal hydride batteries can be repeated 500 charge-discharge cycles by correct operation
- After leaving factory, the emergency battery turns itself into a dormant state to avoid electric discharge and leakage



Controller

- The utilization of wireless IR remote controller:

Button#1: TEST (Press this button, switch to emergency lighting model. Emergency indicator light turns red)

Button#2: DISCHARGE(Press this button, battery starts to discharge, emergency indicator shows up red until electrical discharge process is over. 5 sec later, this lamp switches to normal working state);

- Button#3: STOP
1. Stop discharge (pause discharge when in emergency status)
 2. Cancel automatic discharge (keep pressing button 3 seconds, when red indicator flicker once, means closed every 3 month automatic discharge function.)
 3. Start automatic discharge (keep pressing button 3 seconds, when red indicator continues flicker, means start every 3 month automatic discharge function.)

